

HEIGHT-ADJUSTABLE RECLINING ASSISTED BATHING

Parker



Featuring a distinctive swinging door, Parker® is designed to enable independent to assisted transfers into and out of the tub. Parker is height-adjustable and goes from sitting to reclining, allowing the carer and resident to choose their preferred position to enhance the bathing experience.

ARJO MOBILITY GALLERY



A



B



C



D

Independent and Assisted transfers

Height-adjustable Parker can be positioned in sitting and reclining positions. Its swing-up side door is designed to facilitate smooth access for patients and residents with mobility levels A through C without the need for additional bath lifters. Parker is also appropriate for residents with mobility level D when paired with a ceiling lift.

Multiple levels of anti-scalding protection

Including temperature displays, temperature and pressure regulated mixing valves, and automatic hot water shut off when exceeding safe temperatures.

Enhance the wellness benefits of bathing

Parker offers a choice of still immersion bathing, Air Spa™ and Sound and Vision™ to enhance relaxation and make the most of the wellness benefits of bathing.

Key features

SIDE-ENTRY ACCESS

Integrates with wide range of transfer aids to facilitate independent and assisted transfers for those with limited mobility.

HEIGHT-ADJUSTABLE AND RECLINING

Allows carer to reach preferred working height without compromising resident comfort.

MULTIPLE ANTI-SCALDING PROTECTION FEATURES

SHOWER WAND WITH LOCKABLE TRIGGER

Enables caregiver to activate shower when close to resident.

HEAD AND BACK CUSHIONS (OPTIONAL)

For additional comfort.

INTEGRATED CLEANING AND DISINFECTION SYSTEM (OPTIONAL)

AIR SPA (OPTIONAL)

With nine speed-controlled jet streams.

AUTO-FILL

Automatically fills bath to pre-set water level.

SOUND AND VISION (OPTIONAL)

For an enhanced multisensory experience.



GENERAL

Max safe working load (SWL) (patient + water)	300 kg (661 lbs)
Maximum patient weight	210 kg (463 lbs)
Total weight of tub	126 kg (280 lbs)
Total length in the upright position	1855 mm (73 in)
Total length in reclined position	1960 mm (77 ½ in)
Total width	750 mm (29 ½ in)
Height of door with bathtub in highest position, feet in lowest position	2510 mm (98 ¾ in)
Seat height at lowest position	565 mm (22 ¼ in)
Seat height at highest position	685 mm (27 in)
Water consumption (prefilled foot well volume/autofill level)	96 litres (25.4 gallons)
Water consumption up to overflow level	230 litres (60.8 gallons)
Filling time at 3 bar (43.5 PSI) dynamic pressure (prefill)	1.7 min
Emptying time from auto-fill level	3 min
IP Class according to IEC 60529	IP X4
IP Class hand control and Sound and Vision hand control	IP X7
Maximum static water pressure	6 bar (600 kPa, 87 psi)
Minimum operating pressure (some variants depending on the country)	1 bar (100 kPa, 14.5 psi)

STANDARD FEATURES

- Water temperature display
- Multiple anti-scalding protection functions
- Shower wand with lockable trigger
- Auto-fill
- Overflow
- Lock function for control panel
- Emergency tilting and lowering
- Emergency stop

OPTIONAL FEATURES


- Integrated cleaning and disinfection system
- Air Spa therapy
- Sound & Vision therapy
- Hot water flush kit
- Tub trim available in Blue

ACCESSORIES

- Foot rest, head support and back/seat cushions
- Comfort Collection: Comfort Cushion, Dry Robe, Wet Robe

SPACE REQUIREMENT

Blue area shows the required working area to facilitate transfer and hygiene activities for resident with mobility level A to C while providing adequate access for the resident, equipment and caregiver. Additional space might be required to facilitate transfer of resident with mobility level D using ceiling lift.



For more detailed information visit www.arjo.com